



## **Product Bulletin**

Product Name

Chemical Structure & Description

INCI Name CAS Reg. No.

Applications

Typical Properties

Environmental Effects

Health Effects

Storage & Handling

Workplace Exposure

Clearances

October 2019 Supersedes: September 2019 Page 1 of 2

## **ALPHA-STEP® PC-48**

 $R = C_{10-16}$ 

Sodium Methyl 2-Sulfolaurate and Disodium 2-Sulfolaurate

149458-07-1

ALPHA-STEP PC-48 is an anionic surfactant derived from oleochemicals and its hydrophobic chain distribution, which ranges from C<sub>12</sub> to C<sub>18</sub>, allows for excellent detergency, foaming and mildness properties in a wide variety of household, industrial and personal care applications. ALPHA-STEP PC-48 is appropriate when formulating high foaming, high active personal care products such as body wash. It has a very low viscosity response and is very good at clarifying formulas with high levels of electrolytes. This versatile surfactant also functions well in hard water, having favorable hard water tolerance and lime soap dispersing ability. ALPHA-STEP PC-48 is a readily soluble liquid that can be easily formulated between a pH of 4 to 9. Applications include household and industrial liquid laundry, hand dishwash, hard surface cleaners, hand soaps, specialty foam applications, body washes and facial cleansers.

	• •
Clear yellow liquid	pH, 10% aqueous 6
3 max.	Flash Point (PMCC), °C (°F) >94 (>201)
38.5	Density, g/ml (lbs/U.S. gal) 1.06 (8.8)
43	Viscosity at 25 °C, cps
5 (23)	Critical Micelle Concentration, mg/L 233
8 (18)	RVOC, U.S. EPA 0
5 (41)	Preservative Not required
	3 max. 38.5 43 

Product is readily biodegradable. Additional information available upon request.

ALPHA-STEP PC-48 is expected to have a low oral toxicity (LD50 > 2000 in rats). In-vitro irritation testing show the product to be non-irritating when tested as a neat material (100%). A repeated application soap chamber test shows ALPHA-STEP PC-48 to be a mild material when tested as 1% active.

Normal safety precautions (i.e., gloves and safety goggles) should be employed when handling ALPHA-STEP PC-48. Contact with the eyes and prolonged contact with the skin should be avoided.

It is recommended that ALPHA-STEP PC-48 be stored in sealed containers. Store and handle in equipment normally used for detergents. Recommended storage temperature is 60-100°F (15-38 °C). Material of construction of storage tank should be 316 stainless steel (or fiberglass with DION 382 liner). Transfer pumps should be Viking stainless steel (or other similar gear pump) with internal pressure relief capabilities. The tank and pump should be grounded. If frozen, mild heat and agitation are recommended to ensure material is homogenous before use. Keep product between pH of 4 and 9 or hydrolysis will occur.

Standard Packaging: This product is available in drums, totes and bulk quantities.

Occupational exposure can occur primarily through skin contact or via inhalation of vapors and mists. Engineering controls, personal protective equipment, and other workplace practices should be used to control these exposures.

The international inventories (country clearances) of ALPHA-STEP PC-48 can be found in Section 15 of the Safety Data Sheet (SDS). It is the responsibility of the formulator to review the chemical control regulations for each country where the end product is intended to be sold or used. If you have any further questions regarding

ALPHA-STEP® is a registered trademark of Stepan Company.




inventories, please contact North America Technical Service at techserv@stepan.com.


ALPHA-STEP PC-48 meets Safer Choice screen and is listed on <a href="https://www.cleangredients.org">www.cleangredients.org</a> (an on-line database for green formulators). This product has a maximum use level of 20%. For further information, visit <a href="https://www.cleangredients.org">www.cleangredients.org</a>. Additional Stepan ingredient listing can be found at <a href="https://www.stepan.com">www.stepan.com</a>.

### **Surface Active Properties**

#### Drave's Wetting (0.1% actives at 25°C)

#### Ross-Mile's Foaming (0.1% actives at 25°C)





# Comparative Irritation Data

#### **Fourteen Day Cumulative Irritation Test**

ays to	Number of Da
tation	Produce Irrit
<u>1)</u>	(Score of
	13.50
Least Irritating	5.20
	5.07
	4.27
Most Irritation	2.70

Product Stewardship

Additional Safety Information This product bulletin has been written in accordance with ACC's Product Stewardship guidelines.

A Safety Data Sheet is available upon request.



The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents or to violate any applicable laws. STEPAN COMPANY MAKES NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, AND NO WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE, INCLUDING REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, ADEQUACY OR OTHERWISE. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party in respect of this information, including in respect of its accuracy, completeness, adequacy, furnishing, use, or reliance upon, and the vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.

Stepan



Corporate Headquarters Northfield, Illinois 60093, U.S.A. Phone: 847-446-7500

Fax: 874-501-2100 Website: www.stepan.com For Technical Service Call:
Stepan North America +1-800-745-7837
Stepan Mexico +55-11-5089-2208
Stepan Quimica +55-11-5089-2200
Stepan Colombia +571-636-2808
Stepan Europe +33-476-505-160
Stepan Asia +656-879-9855
Stepan Philippines +656-879-9855

For Customer Service Call:
Stepan North America +1-800-457-7673
Stepan Mexico +52-555-533-1967
Stepan Quimica +55-11-5089-2200
Stepan Colombia +57-6-8993125
Stepan UK +44-161-338-5511
Stepan France +33-476-50-51-00
Stepan Philippines +63-2-842-7951

October 2019 Supersedes: September 2019 Page 2 of 2