

Name INDUSTRIAL DEGREASER WITH STEPOSOL® DG

945 No.

At full strength, this formulation can be used to remove oil, grease, tar, gum, asphalt, fresh paint, Description

adhesives, scuff marks, and lipstick stains. When diluted, it can be used for cleaning walls and floors.

Formulation **INGREDIENTS:** % by Weight

> **Deionized Water** 85.00 **Butyl Cellosolve** 10.00 STEPOSOL® DG 5.00

> **Total** 100.00

Procedure Using vigorous agitation, mix ingredients in order listed.

Physical Appearance at 25°C Clear, colorless liquid

pH, as is **Properties** 30 Viscosity at 25°C cps

8.08 Density, lbs./gal Solids. % 3 > 201

Flash point, °F (PMCC) 4 weeks at 4°C (39°F) Storage/ Stable

6 weeks at Room Temperature Stable 4 weeks at 40°C (104°F) Stable 4 weeks at 50°C (122°F) Stable

Passed

Freeze / Thaw (4 cycles)

Use 1–2 ounces per gallon for cleaning floors and walls. Brush where necessary. Rinse with water. Instructions for Use

Registered **STEPOSOL® Trademarks**

Stability

of Stepan

Company For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or For 011-334-76-505-100 (Europe).

Additional For ordering assistance, call our Account Service Department at 1-800-457-7673. Assistance

Nothing contained herein grants or extends a license, express or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.



Stepan Company

Northfield, Illinois 60093 Telephone (847) 446-7500

Revision Date: 01/18/2010 Publication Date: 07/06/2004 © 2010, Stepan Company. All rights reserved.